



Guidewire Lunderquist

Description

The Lunderquist type Guidewire is built with a single rigid core that facilitates the access of endovascular devices and guarantees, along the axial center, an excellent torque transmission by being Extra Stiff.



Developed to aid in the navigation and positioning of medical devices during percutaneous angioplasty procedures in peripheral arteries. It supports the introduction of angiographic catheters, guides, pre- or post-dilation balloons, as well as peripheral stents, contributing to greater precision and safety in the procedure.

Specifications

- Diameter: 0.035"
- Length: 260cm
- Distal Tip: J
- Rigidity: Extra Stiff
- Coating: Teflon

Codes and references

Code	Measurement
51203	0.035" x 260 cm, JTFe



+55 71 3024 4015
www.msbboxbrasil.com

Araponga Street, 364, Block 01, Lot 19,
Pitangueiras Lauro de Freitas - Bahia - Brazil
- 42701 330

msb@msbboxbrasil.com
 msb-medical-system-do-brasil



WARNING: Product mentioned in this material is intended for use by a physician. Before use, it is important to read the package insert thoroughly for the instructions for use, warnings, and possible complications associated with the use of this device.

Always check the regulatory status of the device in your region. It must not be reproduced, distributed, or extracted. Illustrations are artistic representations only and should not be considered as engineering drawings or photographs.